



TIMBERLUX

TimberLuxFloor.com

TIMBERLUX FLOORING (THAILAND) CO.,LTD

269/35 Moo 8, BO Win Subdistrict, Sriracha District, Chonburi Province, Thailand 20230



**We are
a
Laminate Flooring Manufacturer
In Thailand**

25+ Years of Expertise, Global Warranty Support

เราเป็นโรงงานผลิตพื้นลามิเนตในประเทศไทย

Versatile Bevel Options

Painted V-Groove

Crisp three-dimensional edges deliver a modern and clean aesthetic for contemporary interiors. Perfect for minimalist designs seeking depth and sophistication.

Pressed Bevel



Seamless texture integration mimics the authentic look of natural solid wood flooring, blending timeless charm with modern durability.



Thickness Flexibility

10mm – Light adaptability for versatile applications.

12mm – Enhanced durability and superior sound insulation.



EVA or IXPE Pad attached is Available.

Locking Systems

Unilin® Angle-Angle

Professional-grade installation system for flawless, gap-free results.

Valinge® 5G Dry

Waterproof performance for moisture-prone areas.

DIY-friendly design for long-board installation and gap-free result.

Versatile Length Configurations

Optimize spatial layouts and unleash design creativity with multiple plank length options. Ideal for customized patterns.



2200x234/233mm



1513x235/234mm



1513x195/193mm



1213x195mm



1818/1212/606x195/193mm RL

3D EIR Surface

Embossed-in-Register Wood Grain

Perfectly aligned textures for unmatched realism, replicating the tactile feel of natural wood.
Unprecedented depth and natural authenticity.

Dynamic Gloss Contrast: **4-6° gloss** on flat surfaces & **0° gloss** within recessed grains

Super-Matt EIR Surface

Full 4-6° Gloss Finish

Ultra-matte elegance across all surfaces and recessed grains for a refined, understated look.
Precision-Replicated Textures, Capture the raw beauty of untreated timber, combining rugged charm with modern resilience.

Aqua-Safe

Waterproof core ensures moisture resistance, protecting against spills and humidity.
IN 8% Thickness swelling HDF plus WAX on 4 sides.

Diamond Wear Layer

AC4-Rated durability for heavy commercial or residential use.

Engineered for Every Space

From modern lofts to rustic retreats, our flooring solutions combine artistry, innovation, and uncompromising performance.

Define Your Exclusive-Design is Available!

10 mm Collection Features

WaterProof Laminate IN 8% Thickness Swelling
Made in Thailand with 0% Tariff and 0% Tax



Finish	Bevel	Decor Color	HDF Color	WAX	HDF Compression	Formaldehyde Content	Abrasion Resistance	Warranty	FOB Port	MOQ	Pallet	Production Time
EIR	Painted V-Groove	Available	Brown	Yes	880 Kg/m ³	CARB2 / EPA Certified	AC4	25 years residential limited warranty	Laem Chabang, Thailand	1 Color/Ctr	Engineered Pallet	80 days for first order
	Pressed Bevel Available*							5 years commercial limited warranty	Lat Krabang, Thailand			60 days for back order

UNILIN Angle-Angle Clip	Thickness	Width	Length	PCS/box	Boxes/Skid	Surface Area/Box	Weight/Box	Surface Area/Skid	Weight/Skid	Skid/Ctr	Surface Area/Ctr	Weight/Ctr
10 mm *	195 mm	1213 mm	7.68"	8	5x11=55	1.8923 Sqm	16.7 Kg	104.0754 Sqm	927.5 Kg	40'-28 Skid	2914.1112 Sqm	25970 Kg
	7.68"	47.76"				20.3685 Sqft	36.82 lbs	1120.27 Sqft	2044.79 lbs		31367.493 Sqft	57253.98 lbs
10 mm *	195 mm	1513 mm	7.68"	8	5x11=55	2.3603 Sqm	20.8 Kg	129.8154 Sqm	1156 Kg	40'-22 Skid	2855.9388 Sqm	25432 Kg
	7.68"	59.57"				25.4061 Sqft	45.86 lbs	1397.33 Sqft	2548.54 lbs		30741.3252 Sqft	56067.9 lbs
10 mm *	235 mm	1513 mm	9.25"	6	4x14=56	2.1333 Sqm	18.8 Kg	119.4665 Sqm	1064.8 Kg	40'-24 Skid	2867.1955 Sqm	25555.2 Kg
	9.25"	59.57"				22.9632 Sqft	41.45 lbs	1285.94 Sqft	2347.48 lbs		30862.4926 Sqft	56339.51 lbs
10 mm *	234 mm	2200 mm	9.21"	5	4x14=56	2.574 Sqm	22.7 Kg	144.144 Sqm	1283.2 Kg	40'-20 Skid	2882.88 Sqm	25664 Kg
	9.21"	86.6"				27.7065 Sqft	50.04 lbs	1551.57 Sqft	2828.97 lbs		31031.3203 Sqft	56579.37 lbs

Valinge 2G-2G Clip	Thickness	Width	Length	PCS/box	Boxes/Skid	Surface Area/Box	Weight/Box	Surface Area/Skid	Weight/Skid	Skid/Ctr	Surface Area/Ctr	Weight/Ctr
10 mm	195 mm	1215 mm	7.68"	8	5x11=55	1.8954 Sqm	16.7 Kg	104.247 Sqm	927.7 Kg	40'-28 Skid	2918.916 Sqm	25975.6 Kg
	7.68"	47.84"				20.4021 Sqft	36.82 lbs	1122.11 Sqft	2045.23 lbs		31419.2118 Sqft	57266.33 lbs
10 mm	195 mm	1515 mm	7.68"	8	5x11=55	2.3634 Sqm	20.8 Kg	129.987 Sqm	1156.2 Kg	40'-22 Skid	2859.714 Sqm	25436.4 Kg
	7.68"	59.65"				25.4396 Sqft	45.86 lbs	1399.18 Sqft	2548.98 lbs		30781.9615 Sqft	56077.6 lbs
10 mm	235 mm	1515 mm	9.25"	6	4x14=56	2.1362 Sqm	18.8 Kg	119.6244 Sqm	1065 Kg	40'-24 Skid	2870.9856 Sqm	25560 Kg
	9.25"	59.65"				22.9935 Sqft	41.45 lbs	1287.64 Sqft	2347.92 lbs		30903.289 Sqft	56350.09 lbs

Valinge 5G DRY Clip	Thickness	Width	Length	PCS/box	Boxes/Skid	Surface Area/Box	Weight/Box	Surface Area/Skid	Weight/Skid	Skid/Ctr	Surface Area/Ctr	Weight/Ctr
10 mm	193 mm	1513 mm	7.6"	8	5x11=55	2.3361 Sqm	20.6 Kg	128.484 Sqm	1145 Kg	40'-22 Skid	2826.6471 Sqm	25190 Kg
	7.6"	59.57"				25.1455 Sqft	45.42 lbs	1383 Sqft	2524.29 lbs		30426.0296 Sqft	55534.38 lbs
10 mm	234 mm	1513 mm	9.21"	6	4x14=56	2.1243 Sqm	18.7 Kg	118.9581 Sqm	1059.2 Kg	40'-24 Skid	2854.9947 Sqm	25420.8 Kg
	9.21"	59.57"				22.8654 Sqft	41.23 lbs	1280.47 Sqft	2335.13 lbs		30731.1628 Sqft	56043.2 lbs
10 mm	233 mm	2200 mm	9.17"	5	4x14=56	2.563 Sqm	22.6 Kg	143.528 Sqm	1277.6 Kg	40'-20 Skid	2870.56 Sqm	25552 Kg
	9.17"	86.6"				27.5881 Sqft	49.82 lbs	1544.94 Sqft	2816.62 lbs		30898.7078 Sqft	56332.45 lbs

12mm Collection Features

WaterProof Laminate IN 8% Thickness Swelling
Made in Thailand with 0% Tariff and 0% Tax



Finish	Bevel	Decor Color	HDF Color	WAX	HDF Compression	Formaldehyde Content	Abrasion Resistance	Warranty	FOB Port	MOQ	Pallet	Production Time
EIR	Painted V-Groove	Available	Brown	Yes	880 Kg/m³	CARB2 / EPA Certified	AC4	25 years residential limited warranty	Laem Chabang, Thailand	1 Color/Ctr	Engineered Pallet	80 days for first order
	Pressed Bevel Available*							5 years commercial limited warranty	Lat Krabang, Thailand			60 days for back order

UNILIN Angle-Angle Clip	Thickness	Width	Length	PCS/box	Boxes/Skid	Surface Area/Box	Weight/Box	Surface Area/Skid	Weight/Skid	Skid/Ctr	Surface Area/Ctr	Weight/Ctr
	12 mm *	195 mm	1213 mm	7	5x10=50	1.6557 Sqm	17.5 Kg	82.7873 Sqm	884 Kg	40'-28 Skid	2318.043 Sqm	24752 Kg
		7.68"	47.76"			17.8224 Sqft	38.58 lbs	891.12 Sqft	1948.88 lbs		24951.4149 Sqft	54568.75 lbs
	12 mm *	195 mm	1513 mm	6	5x12=60	1.7702 Sqm	18.7 Kg	106.2126 Sqm	1134 Kg	40'-22 Skid	2336.6772 Sqm	24948 Kg
		7.68"	59.57"			19.0545 Sqft	41.23 lbs	1143.27 Sqft	2500.04 lbs		25151.9934 Sqft	55000.86 lbs
	12 mm *	235 mm	1513 mm	5	4x14=56	1.7778 Sqm	18.8 Kg	99.5554 Sqm	1064.8 Kg	40'-24 Skid	2389.3296 Sqm	25555.2 Kg
		9.25"	59.57"			19.136 Sqft	41.45 lbs	1071.61 Sqft	2347.48 lbs		25718.7438 Sqft	56339.51 lbs
	12 mm *	234 mm	2200 mm	4	4x14=56	2.0592 Sqm	21.7 Kg	115.3152 Sqm	1227.2 Kg	40'-20 Skid	2306.304 Sqm	24544 Kg
		9.21"	86.6"			22.1652 Sqft	47.84 lbs	1241.25 Sqft	2705.51 lbs		24825.0563 Sqft	54110.19 lbs
	12mm	195 mm	1818/1212/606 RL	3+3+3	5x11=55	2.1271 Sqm	22.5 Kg	116.9883 Sqm	1249.5 Kg	40'-20 Skid	2339.766 Sqm	24990 Kg
		7.68"	71.6"/47.7"/23.9" RL			22.8957 Sqft	49.6 lbs	1259.26 Sqft	2754.67 lbs		25185.2412 Sqft	55093.45 lbs

Valinge 5G DRY Clip	Thickness	Width	Length	PCS/box	Boxes/Skid	Surface Area/Box	Weight/Box	Surface Area/Skid	Weight/Skid	Skid/Ctr	Surface Area/Ctr	Weight/Ctr
	12 mm	193 mm	1513 mm	6	5x12=60	1.7521 Sqm	18.5 Kg	105.1232 Sqm	1122 Kg	40'-22 Skid	2312.7113 Sqm	24684 Kg
		7.6"	59.57"			18.8591 Sqft	40.79 lbs	1131.55 Sqft	2473.58 lbs		24894.0242 Sqft	54418.84 lbs
	12 mm	234 mm	1513 mm	5	4x14=56	1.7702 Sqm	18.7 Kg	99.1318 Sqm	1059.2 Kg	40'-24 Skid	2379.1622 Sqm	25420.8 Kg
		9.21"	59.57"			19.0545 Sqft	41.23 lbs	1067.05 Sqft	2335.13 lbs		25609.3024 Sqft	56043.2 lbs
	12 mm	233 mm	2200 mm	4	4x14=56	2.0504 Sqm	21.7 Kg	114.8224 Sqm	1227.2 Kg	40'-20 Skid	2296.448 Sqm	24544 Kg
		9.17"	86.6"			22.0705 Sqft	47.84 lbs	1235.95 Sqft	2705.51 lbs		24718.9663 Sqft	54110.19 lbs
	12 mm	193 mm	1818/1212/606 RL	3+3+3	5x11=55	2.1052 Sqm	22.2 Kg	115.7884 Sqm	1233 Kg	40'-20 Skid	2315.7684 Sqm	24660 Kg
		7.6"	71.6"/47.7"/23.9" RL			22.6608 Sqft	48.94 lbs	1246.35 Sqft	2718.3 lbs		24926.9311 Sqft	54365.93 lbs

Note